

SI / Gaussian Formula Conversion Table

D.G. Simpson, Ph.D.

Department of Physical Sciences and Engineering
Prince George's Community College

January 18, 2013

This table may be used to convert any electromagnetic formula between SI units and Gaussian units; simply make the substitutions indicated. To simplify the results, you may use $\epsilon_0\mu_0 = 1/c^2$.

Note that in SI units there are two conventions for magnetic pole strength and dipole moment: one based on the B field (pole strength in A m), and one based on the H field (pole strength in Wb). Both conventions are given here.

As an example, given Coulomb's law in Gaussian units ($F = q_1q_2/r^2$), we use the table to create the corresponding equation in SI units: $F = (q_1/\sqrt{4\pi\epsilon_0})(q_2/\sqrt{4\pi\epsilon_0})/r^2 = (1/4\pi\epsilon_0)q_1q_2/r^2$.

SI / Gaussian Formula Conversion Table.

Quantity	Gaussian Units	SI Units
Electric field	\mathbf{E}	$\sqrt{4\pi\epsilon_0}\mathbf{E}$
Electric potential	V	$\sqrt{4\pi\epsilon_0}V$
Electric displacement	\mathbf{D}	$\sqrt{4\pi/\epsilon_0}\mathbf{D}$
Electric charge	q	$q/\sqrt{4\pi\epsilon_0}$
Electric charge density	ρ	$\rho/\sqrt{4\pi\epsilon_0}$
Electric current	I	$I/\sqrt{4\pi\epsilon_0}$
Electric current density	\mathbf{J}	$\mathbf{J}/\sqrt{4\pi\epsilon_0}$
Electric polarization	\mathbf{P}	$\mathbf{P}/\sqrt{4\pi\epsilon_0}$
Electric dipole moment	\mathbf{p}	$\mathbf{p}/\sqrt{4\pi\epsilon_0}$
Magnetic induction	\mathbf{B}	$\sqrt{4\pi/\mu_0}\mathbf{B}$
Magnetic flux	Φ_B	$\sqrt{4\pi/\mu_0}\Phi_B$
Magnetic vector potential	\mathbf{A}	$\sqrt{4\pi/\mu_0}\mathbf{A}$
Magnetic scalar potential	φ^*	$\sqrt{4\pi\mu_0}\varphi^*$
Magnetic intensity	\mathbf{H}	$\sqrt{4\pi\mu_0}\mathbf{H}$
Magnetomotive force	mmf	$\sqrt{4\pi\mu_0}$ mmf

SI / Gaussian Formula Conversion Table.

Quantity	Gaussian Units	SI Units
Magnetic pole strength (B conv.)	q^*	$\sqrt{\mu_0/4\pi} q^*$
Magnetic moment (B conv.)	\mathbf{m}	$\sqrt{\mu_0/4\pi} \mathbf{m}$
Magnetization	\mathbf{M}	$\sqrt{\mu_0/4\pi} \mathbf{M}$
Magnetic pole strength (H conv.)	Q^*	$Q^* / \sqrt{4\pi\mu_0}$
Magnetic moment (H conv.)	\mathbf{d}	$\mathbf{d} / \sqrt{4\pi\mu_0}$
Electric permittivity	ϵ	ϵ/ϵ_0
Magnetic permeability	μ	μ/μ_0
Electric susceptibility	χ_e	$\chi_e/4\pi$
Magnetic susceptibility	χ_m	$\chi_m/4\pi$
Conductivity	σ	$\sigma/4\pi\epsilon_0$
Conductance	S	$S/4\pi\epsilon_0$
Capacitance	C	$C/4\pi\epsilon_0$
Resistivity	ρ	$4\pi\epsilon_0\rho$
Resistance	R	$4\pi\epsilon_0 R$
Inductance	L	$4\pi\epsilon_0 L$
Memristance	M	$4\pi\epsilon_0 M$
Magnetic reluctance	\mathcal{R}	$\mu_0 \mathcal{R}$